

**56.07 INTEGRATED WATER MANAGEMENT**

29/10/2015  
VC101

**56.07-1 Drinking water supply objectives**

09/10/2006  
VC42

To reduce the use of drinking water.

To provide an adequate, cost-effective supply of drinking water.

**Standard C22**

The supply of drinking water must be:

- Designed and constructed in accordance with the requirements and to the satisfaction of the relevant water authority.
- Provided to the boundary of all lots in the subdivision to the satisfaction of the relevant water authority.

**56.07-2 Reused and recycled water objective**

29/10/2015  
VC101

To provide for the substitution of drinking water for non-drinking purposes with reused and recycled water.

**Standard C23**

Reused and recycled water supply systems must be:

- Designed, constructed and managed in accordance with the requirements and to the satisfaction of the relevant water authority, Environment Protection Authority and Department of Health and Human Services.
- Provided to the boundary of all lots in the subdivision where required by the relevant water authority.

**56.07-3 Waste water management objective**

09/10/2006  
VC42

To provide a waste water system that is adequate for the maintenance of public health and the management of effluent in an environmentally friendly manner.

**Standard C24**

Waste water systems must be:

- Designed, constructed and managed in accordance with the requirements and to the satisfaction of the relevant water authority and the Environment Protection Authority.
- Consistent with any relevant approved domestic waste water management plan.

Reticulated waste water systems must be provided to the boundary of all lots in the subdivision where required by the relevant water authority.

**56.07-4 Urban run-off management objectives**

09/10/2006  
VC42

To minimise damage to properties and inconvenience to residents from urban run-off.

To ensure that the street operates adequately during major storm events and provides for public safety.

To minimise increases in stormwater run-off and protect the environmental values and physical characteristics of receiving waters from degradation by urban run-off.

### **Standard C25**

The urban stormwater management system must be:

- Designed and managed in accordance with the requirements and to the satisfaction of the relevant drainage authority.
- Designed and managed in accordance with the requirements and to the satisfaction of the water authority where reuse of urban run-off is proposed.
- Designed to meet the current best practice performance objectives for stormwater quality as contained in the Urban Stormwater – Best Practice Environmental Management Guidelines (Victorian Stormwater Committee 1999) as amended.
- Designed to ensure that flows downstream of the subdivision site are restricted to pre-development levels unless increased flows are approved by the relevant drainage authority and there are no detrimental downstream impacts.

The stormwater management system should be integrated with the overall development plan including the street and public open space networks and landscape design.

For all storm events up to and including the 20% Average Exceedence Probability (AEP) standard:

- Stormwater flows should be contained within the drainage system to the requirements of the relevant authority.
- Ponding on roads should not occur for longer than 1 hour after the cessation of rainfall.

For storm events greater than 20% AEP and up to and including 1% AEP standard:

- Provision must be made for the safe and effective passage of stormwater flows.
- All new lots should be free from inundation or to a lesser standard of flood protection where agreed by the relevant floodplain management authority.
- Ensure that streets, footpaths and cycle paths that are subject to flooding meet the safety criteria  $d_a V_{ave} < 0.35 \text{ m}^2/\text{s}$  (where,  $d_a$  = average depth in metres and  $V_{ave}$  = average velocity in metres per second).

The design of the local drainage network should:

- Ensure run-off is retarded to a standard required by the responsible drainage authority.
- Ensure every lot is provided with drainage to a standard acceptable to the relevant drainage authority. Wherever possible, run-off should be directed to the front of the lot and discharged into the street drainage system or legal point of discharge.
- Ensure that inlet and outlet structures take into account the effects of obstructions and debris build up. Any surcharge drainage pit should discharge into an overland flow in a safe and predetermined manner.
- Include water sensitive urban design features to manage run-off in streets and public open space. Where such features are provided, an application must describe maintenance responsibilities, requirements and costs.

Any flood mitigation works must be designed and constructed in accordance with the requirements of the relevant floodplain management authority.